



EZPLC



EZPLCX-X-48 Specifications

**EZPLC
Snap-in I/O
EZPLCX-X-48X**



**EZPLC Plus
Screw-down I/O
EZPLCP-X-48X**

Modules not included with base.

Model Number	Interface	Price	Del.
EZPLC-A-48 EZPLCP-A-48	AC Model – 48 I/O Base comes with RS232 port 1 and RS422/485 port 2, and a Male connector for plugging in DeviceNet or Profibus option cards. EZPLC has snap-in I/O where as EZPLCP has screw-down I/O.		STK
EZPLC-A-48E EZPLCP-A-48E	AC Model – 48 I/O Enhanced Ethernet Base comes with RS232 port 1, RS422/485 port 2, Ethernet port 3 and a Male connector for plugging in DeviceNet or Profibus option cards. EZPLC has snap-in I/O where as EZPLCP has screw-down I/O.		3DAY
EZPLC-D-48 EZPLCP-D-48	DC Power – 48 I/O Base comes with RS232 port 1 and RS422/485 port 2, and a Male connector for plugging in DeviceNet or Profibus option cards. EZPLC has snap-in I/O where as EZPLCP has screw-down I/O.		STK
EZPLC-D-48E EZPLCP-D-48E	DC Power – 48 I/O Enhanced Ethernet Base comes with RS232 port 1, RS422/485 port 2, Ethernet port 3 and a Male connector for plugging in DeviceNet or Profibus option cards. EZPLC has snap-in I/O where as EZPLCP has screw-down I/O.		3DAY

No limitation on I/O module location except: 1) Bottom left module cannot be AC output module; 2) Analog input and output combination module can be configured only in the first 4 slots

