



EZPLC



EZPLCX-X-96 Specifications



**EZPLC Plus
Screw-down I/O
EZPLCP-X-96X**

**EZPLC
Snap-in I/O
EZPLCX-X-96X**

Modules not included with base.

Model Number	Interface	Price	Del.
EZPLC-A-96 EZPLCP-A-96	AC Model – 96 I/O Base comes with RS232 port 1 and RS422/485 port 2, and a Male connector for plugging in DeviceNet or Profibus option cards. EZPLC has snap-in I/O where as EZPLCP has screw-down I/O.		3DAY
EZPLC-A-96E EZPLCP-A-96E	AC Model – 96 I/O Enhanced Ethernet Base comes with RS232 port 1, RS422/485 port 2, Ethernet port 3 and a Male connector for plugging in DeviceNet or Profibus option cards. EZPLC has snap-in I/O where as EZPLCP has screw-down I/O.		3DAY
EZPLC-D-96 EZPLCP-D-96	DC Power – 96 I/O Base comes with RS232 port 1 and RS422/485 port 2, and a Male connector for plugging in DeviceNet or Profibus option cards. EZPLC has snap-in I/O where as EZPLCP has screw-down I/O.		3DAY
EZPLC-D-96E EZPLCP-D-96E	DC Power – 96 I/O Enhanced Ethernet Base comes with RS232 port 1, RS422/485 port 2, Ethernet port 3 and a Male connector for plugging in DeviceNet or Profibus option cards. EZPLC has snap-in I/O where as EZPLCP has screw-down I/O.		3DAY

No limitation on I/O module location except: 1) Bottom left module cannot be AC output module; 2) Analog input and output combination module can be configured only in the first 4 slots; 3) Analog I/O modules can be configured only in the first 10 slots.

